



FIREMAN'S SUIT AND BREATHING DEVICES

VULCAN F2 FIREMAN'S OUTFIT

SHM's Vulcan F2 Fireman's outfit, complying to SOLAS standard, has been designed to provide protection from the exposure of heat in the event of a fire. The outfit consists of a heat insulation suit, constructed from flame-resistant fabric with aluminum coating, pair of gloves, helmet with visor, fire hood, rubber boots and accessories.



SKU: 2221100029

Accessories



Fireman's Boots
2222100004



Fireman's helmet
2223100001



Fireman's Gloves
2221100039



Axe with Insulated Handle
2224100001



Axe with Long Wooden Handle
2224100002



Fire Proof Line
2258100010 | 2225100001



Explosion Proof Torch
2226100010



Axe Pouch | Fireman's Waistbelt
2224100003 | 2221100007



Dura 104
4171100004



Helmet Visor
2223100002



Neck Cover
2223100010



Hood
2221100045



SELF-CONTAINED BREATHING APPARATUS SET, WITH DSU

Aether self-contained open-circuit compressed air breathing apparatus, complying to SOLAS standards, is designed to provide respiratory protection from toxic gases and smoke to the user, while entering or escaping a hazardous environment.

The complete set includes a face mask, demand valve, backplate with harness, cylinder and regulator.



SPECIFICATIONS

Product Code	: 2241100010
Cylinder Volume	: 6 L
Air Capacity	: 1,800 L
Working Pressure	: 300 Bar
Service Time	: 55-60 mins
Alarm Pressure	: 40-60 Bar
Weight	: ≤18 kg



Carrying Case | F06112

ACCESSORIES

Cylinder	Valve	Face Mask	Pressure Tester	Backplate & Harness	Demand Valve
					
2243100003	2243100001	2243100004	2243100005	2243100006	2243100007

AETHER EMERGENCY ESCAPE BREATHING DEVICE



Aether EBD's are used to safely evacuate from a dangerous environment that lacks normal breathing conditions. Such situations arise from smoke caused by fire, gas leaks, etc.

The complete set includes a face hood connected to the cylinder in a carry case and complies to SOLAS standards.



SPECIFICATIONS

Aether EBD - 15

Product Code	2242100001
Air Capacity	3 L
Air Flow (L/Min)	≥35
Working Pressure	210 Bar
Service Time	≥15 mins
Alarm Pressure	40-60 Bar
Weight	≤8.5 kg
Working Temperature	-10°C + 65°C

ACCESSORIES

Face Hood



2244100003

Cylinder Valve



2244100001

Spare Cylinder



2244100002
3L

Refilling Adapter



2244100014