



INFLATABLE
LIFERAFT

THROW OVER-BOARD LIFERAFT

SHM's range of Throw Over-Board Liferafts are manufactured to the highest quality standards, under close supervision of international classification societies. Standard SOLAS Liferafts are available in capacity of 6, 10, 15, 20 & 25 persons to suit vessel's safety plan and are designed to function in adverse sea conditions (-30C+60 C).

KEY FEATURES


- Comply to SOLAS LSA Code 96 including latest amendments in the year 2010 i.e. MSC Res.218(82), 226(82), 293(87) & 295(87)).
- Approved by Directorate General of Shipping India and Ministry of Surface Transport, which are both representative bodies of the Govt. of India.
- Manufactured from polyester neoprene coated fabric that complies to MSC Resolution 81/70 for excellent weather resistance and permeability.
- Two buoyancy chambers ensures that with failure of one, the other provides sufficient buoyancy to carry passengers safely.
- Drop tested for maximum stowage height of 35 meters.



ACCESSORIES



Hydrostatic Release Unit (HRU)
SKU: 3157100002



Deck Cradles
SKU: 3156100006



Column Racks
SKU: 3156100007

MODEL NO.	SKU CODE	CAPACITY	PHYSICAL FORM	CONSTRUCTION OF CANOPY ARCH	WIDTH (mm) (A)	HEIGHT (mm) (B)	WORKING PRESSURE (in mm, wg)	CONTAINER DIMENSIONS	
								LENGTH (mm) (C)	DIAMETER (mm) (D)
A-6 (II)	3091100029	6			2116	1220	1400	1245	520
A-10 (II)	3092100012	10			2720	1400	1400	1260	635
A-15 (II)	3093100019	15			3360	1680	1400	1420	635
A-20 (II)	3094100026	20			3820	1900	1400	1495	737
A-25 (II)	3095100026	25			4220	2100	1400	1495	737